

368F & 368R

DESCRIPTION

- Industrial protective glove.
- Green synthetic unsupported glove.
- Available in flocked or unflocked version.
- 4 sizes available : 8, 9, 10 and 11.
- Trade unit: 6 pairs, 72 pairs in a transit case.

CHARACTERISTICS

- Nitrile unsupported glove.
- Flock lined 100 % cotton for 368F version.
- Longer gauntlet style cuff for extra protection.
- Length: 17" approx.
- Single wall thickness : 22mil approx.

PERFORMANCES

- High resistance to many solvents and oil based chemicals.
- Good resistance to abrasion.
- Resistant and flexible, suitable for many industrial applications.
- A tough chemical resistant glove with long elbow length cuff for extra protection.
- In compliance with the standards EN420 (General requirements), EN388 (Mechanical Hazards) and EN374 (Chemical and Micro-organisms Hazards) by the notified laboratory BSI.
- Manufactured under EC quality assurance system carried out by the BSI.

APPLICATIONS

- CE Complex Design.
- Ideal for handling aggressive oil based chemicals.
- Applications : chemical, automotive, printing and petroleum related industries.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests, and manufactured under a CE quality assurance system carried out by a notified body.

CE 0086



EN 420

EN 420

5 Dexterity

EN 388

4 Abrasion

1 Cut

0 Tear

2 Puncture

EN 374

4 A - Methanol

2 G - Diethylamine

6 J - N-heptane

6 K - Caustic soda solution 40 %

4 L - Sulfuric acid 96 %



4102

EN 388

Mechanical hazards



AGJKL

EN 374

Chemical hazards



EN 374

Micro-organism hazards

Order codes

Sizes	8 (M)	9 (L)	10 (XL)	11 (XXL)
368F	06475	06476	06477	06478
368R	06482	06483	06484	06485